

AUTO SHUT-OFF VALVE(GENERAL,OUTDOOR,EXPLOSION PROOF TYPE) AND CONTROLLER

- GAS SHUT-OFF DEVICE WITH CONTROLLER (OUTDOOR TYPE)(15A, 20A, 25A)

Model : SHT-815A, 820A, 825A
SHT-820AW, 825AW(Outdoor type)

Description

- ◆ AUTO SHUT-OFF VALVE
- ◆ MODEL : SHT-820

Features

- OP/CL at long range and shut-off valve automatically
- Monitor the open/close state on controller
- Prompt shut-off valve prevent an accident
- Easy expansion(OPTION)
- Minimize the size and power consumption
- Auto shut off valve apply to system of range of plant or heating and cooling system.

Specification

CONTROLLER		SHUT-OFF DEVICE	
Model No.	SHT-820(2.Channel) (Wallmount type) SHT-ASV(P) (insert type on SHT-970)	Model No.	SHT-815A, 820A, 825A SHT-820AW, 825AW(Outdoor type)
Type	Auto shut-off valve controller	Operating power	12V.DC
Operating power	110~220V.AC, 50/60Hz	Gas pipe size	15A, 20A, 25A
Consumption electric power	0.5W(Normal), 2W(Alarm)	Shut-off time	Less than 15sec
Control type	Time control type(30sec)	Open/Close angle	90℃(limit switch type)
Receive type	Current sensitive (From Detector)	Body material	PC/ABS injection molding
Alarm input line	2.Channel	Gear material	POLY ACETYL COPOLYMER
Alarm type	BUZZER	Use valve	Ball valve
Output signal	12V.DC	Operating type	Operate the valve
Display type	(LED) Open-Green / Close-Yellow / Alarm-Red	Installation type	Tightening the pipeline's volt
Open/Close type	Manual and automatic open,close	Operating temp'/humi'	-40℃~+70℃/Less than 95%
Operating temp'/humi'	-40℃~+70℃/Less than 95%	Cable	CW or VCTF 1.5sq x 2wire
Power input cable	110~220V.AC POWER - 2wire	Weight	0.35Kgs
Detector input cable	2wire		
Shut-off device output	2wire(Red+, Black-)		
Weight	0.15Kgs		

외형도
(Dimension)

